

Nominal Size	Wall	Schedule	Pipe Weight per Foot	Footage per Truckload Bare		Footage per Truckload Fusion Bond Coated		Footage per Truckload TGF-3 Coated		Footage per Truckload Plastic Coated	
				Pyramid	Strip	Pyramid	Strip	Pyramid	Strip	Pyramid	Strip
2"	0.125		3.01	14,967	14,967	14,594	14,594	12,582	12,582	14,347	14,347
2"	0.154	40/STD	3.66	12,307	12,307	12,054	12,054	10,648	10,648	11,885	11,885
2"	0.218	80/XH	5.03	8,952	8,952	8,817	8,817	8,040	8,040	8,726	8,726
2"	0.343	160	7.45	6,040	6,040	5,978	5,978	5,611	5,611	5,936	5,936
2½"	0.125		3.67	12,246	12,246	11,944	11,944	10,310	10,310	11,735	11,735
2½"	0.203	40/STD	5.80	7,761	7,761	7,638	7,638	6,935	6,935	7,552	7,552
2½"	0.276	80/XH	7.67	5,868	5,868	5,798	5,798	5,384	5,384	5,748	5,748
2½"	0.375	160	10.02	4,490	4,490	4,449	4,449	4,201	4,201	4,420	4,420
3"	0.125		4.51	9,978	9,978	9,734	9,734	8,411	8,411	9,514	9,514
3"	0.156		5.58	8,069	8,069	7,909	7,909	7,013	7,013	7,763	7,763
3"	0.188		6.66	6,761	6,761	6,648	6,648	6,003	6,003	6,544	6,544
3"	0.216	40/STD	7.58	5,934	5,934	5,847	5,847	5,343	5,343	5,767	5,767
3"	0.300	80/XH	10.26	4,385	4,385	4,337	4,337	4,053	4,053	4,293	4,293
3"	0.438	160	14.34	3,139	3,139	3,114	3,114	2,965	2,965	3,091	3,091
3½"	0.226	40/STD	9.12	4,935	4,935	4,867	4,867	4,465	4,465	4,804	4,804
3½"	0.318	80/XH	12.52	3,595	3,595	3,559	3,559	3,339	3,339	3,525	3,525
4"	0.125		5.85	7,697	7,697	7,511	7,511	6,497	6,497	7,346	7,346
4"	0.156		7.24	6,212	6,212	6,090	6,090	5,406	5,406	5,981	5,981
4"	0.188		8.67	5,193	5,193	5,107	5,107	4,617	4,617	5,030	5,030
4"	0.237	40/STD	10.80	4,166	4,166	4,111	4,111	3,788	3,788	4,061	4,061
4"	0.337	80/XH	15.00	3,001	3,001	2,972	2,972	2,799	2,799	2,946	2,946
4"	0.438	120	19.02	2,366	2,366	2,348	2,348	2,239	2,239	2,332	2,332
4½"	0.247	STD	12.55	3,586	3,586	3,545	3,545	3,302	3,302	3,507	3,507
4½"	0.355	XH	17.63	2,553	2,553	2,532	2,532	2,405	2,405	2,513	2,513
5"	0.258	40/STD	14.63	3,076	3,076	3,037	3,037	2,821	2,821	3,000	3,000
5"	0.375	80/XH	20.80	2,164	2,164	2,145	2,145	2,035	2,035	2,126	2,126
5"	0.500	120	27.06	1,663	1,663	1,652	1,652	1,586	1,586	1,640	1,640
6"	0.125		8.69	3,780	5,181	3,780	5,056	3,570	4,388	3,570	4,926
6"	0.156		10.79	3,780	4,171	3,780	4,090	3,570	3,641	3,570	4,004
6"	0.188		12.94	3,479	3,479	3,422	3,422	3,102	3,102	3,362	3,362
6"	0.219		15.00	3,001	3,001	2,958	2,958	2,716	2,716	2,913	2,913
6"	0.250		17.04	2,641	2,641	2,609	2,609	2,418	2,418	2,573	2,573
6"	0.280	40/STD	18.99	2,369	2,369	2,343	2,343	2,189	2,189	2,315	2,315
6"	0.432	80/XH	28.60	1,573	1,573	1,562	1,562	1,492	1,492	1,549	1,549
6"	0.562	120	36.43	1,235	1,235	1,228	1,228	1,184	1,184	1,220	1,220
8"	0.156		14.12	2,268	3,186	2,268	3,125	2,268	2,784	2,268	3,058
8"	0.188		16.96	2,268	2,654	2,268	2,611	2,268	2,369	2,268	2,565
8"	0.219		19.68	2,268	2,287	2,255	2,255	2,072	2,072	2,220	2,220
8"	0.250	20	22.38	2,011	2,011	1,986	1,986	1,843	1,843	1,959	1,959
8"	0.277	30	24.72	1,820	1,820	1,800	1,800	1,682	1,682	1,778	1,778
8"	0.322	40/STD	28.58	1,575	1,575	1,559	1,559	1,470	1,470	1,543	1,543
8"	0.500	80/XH	43.43	1,036	1,036	1,030	1,030	990	990	1,022	1,022
8"	0.594	100	51.00	882	882	878	878	848	848	872	872
10"	0.188		21.23	1,470	2,120	1,470	2,086	1,470	1,893	1,470	2,049
10"	0.219		24.65	1,470	1,825	1,470	1,800	1,470	1,655	1,470	1,773
10"	0.250	20	28.06	1,470	1,604	1,470	1,584	1,470	1,471	1,470	1,563
10"	0.279		31.23	1,441	1,441	1,425	1,425	1,333	1,333	1,408	1,408
10"	0.307	30	34.27	1,313	1,313	1,300	1,300	1,222	1,222	1,286	1,286
10"	0.365	40/STD	40.52	1,111	1,111	1,101	1,101	1,045	1,045	1,091	1,091
10"	0.500	60/XH	54.79	821	821	816	816	785	785	811	811
10"	0.594	80	64.49	698	698	694	694	671	671	690	690

Above calculations are based upon the following:

1. Loading 45,000#/s maximum/truck.
2. Trailer width of 96" (some trailers are 102").
3. The maximum load height is 13'6".
4. The pipe and coating weights are theoretical. Please verify for each individual requirement.

(713) 799-9235
 FAX (713) 799-8701
 Web Site: www.texaspipe.com
 E-mail: tps@texaspipe.com

Nominal Size	Wall	Schedule	Pipe Weight per Foot	Footage per Truckload Bare		Footage per Truckload Fusion Bond Coated		Footage per Truckload TGF-3 Coated		Footage per Truckload Plastic Coated	
				Pyramid	Strip	Pyramid	Strip	Pyramid	Strip	Pyramid	Strip
12"	0.188		25.25	1,134	1,782	1,134	1,754	1,134	1,593	1,134	1,723
12"	0.219		29.34	1,134	1,534	1,134	1,513	1,134	1,392	1,134	1,490
12"	0.250	20	33.41	1,134	1,347	1,134	1,331	1,134	1,236	1,134	1,313
12"	0.281		37.46	1,134	1,201	1,134	1,188	1,112	1,112	1,174	1,174
12"	0.312		41.48	1,085	1,085	1,074	1,074	1,012	1,012	1,062	1,062
12"	0.330	30	43.81	1,027	1,027	1,018	1,018	961	961	1,007	1,007
12"	0.375	STD	49.61	907	907	900	900	855	855	891	891
12"	0.406	40	53.57	840	840	834	834	795	795	827	827
12"	0.500	XH	65.48	687	687	683	683	657	657	678	678
12"	0.562	60	73.22	615	615	611	611	590	590	607	607
12"	0.688	80	88.71	507	507	505	505	491	491	502	502
14"	0.188	10	27.76	840	1,512	840	1,512	840	1,449	840	1,567
14"	0.219		32.26	840	1,395	840	1,376	840	1,266	840	1,354
14"	0.250	10	36.75	840	1,225	840	1,210	840	1,124	840	1,193
14"	0.312	20	45.65	840	986	840	976	840	919	840	965
14"	0.375	30/STD	54.62	824	824	817	817	777	777	810	810
14"	0.438	40	63.50	709	709	704	704	674	674	698	698
14"	0.500	XH	72.16	624	624	620	620	596	596	615	615
14"	0.594	60	85.13	529	529	526	526	509	509	523	523
16"	0.219		36.95	840	1,218	840	1,201	840	1,105	840	1,183
16"	0.250	10	42.09	840	1,069	840	1,056	840	981	840	1,042
16"	0.281		47.22	840	953	840	943	840	883	840	931
16"	0.312	20	52.32	840	860	840	852	802	802	840	842
16"	0.375	30/STD	62.64	718	718	713	713	678	678	706	706
16"	0.500	40/XH	82.85	543	543	540	540	520	520	536	536
16"	0.656	60	107.60	418	418	416	416	404	404	414	414
18"	0.250	10	47.44	588	840	588	937	588	871	588	921
18"	0.312	20	58.99	588	763	588	755	588	712	588	745
18"	0.375	STD	70.65	588	637	588	632	588	601	588	624
18"	0.500	XH	93.54	481	481	478	478	460	460	474	474
18"	0.562	40	104.76	430	430	427	427	413	413	424	424
18"	0.750	60	138.30	325	325	324	324	316	316	322	322
20"	0.250	10	52.78	588	840	588	842	588	783	588	827
20"	0.312		65.66	588	685	588	679	588	640	588	669
20"	0.375	20/STD	78.67	572	572	567	567	540	540	561	561
20"	0.500	30/XH	104.23	432	432	429	429	413	413	425	425
20"	0.594	40	123.23	365	365	363	363	352	352	361	361
20"	0.750		154.34	292	292	290	290	283	283	289	289
22"	0.250	10	58.13	378	672	378	672	378	672	378	672
22"	0.375	20/STD	86.69	378	519	378	515	378	490	378	508
22"	0.500	30/XH	114.92	378	392	378	389	375	375	378	385
22"	0.688	40	156.74	287	287	286	286	278	278	284	284
22"	0.750		170.37	264	264	263	263	256	256	261	261
24"	0.250	10	63.47	378	504	378	504	378	504	378	504
24"	0.312		79.01	378	504	378	504	378	504	378	504
24"	0.375	20/STD	94.71	378	475	378	475	378	448	378	465
24"	0.500	XH	125.61	358	358	378	358	343	343	352	352
24"	0.562	30	140.81	320	320	320	320	307	307	315	315
24"	0.688	40	171.45	262	262	262	262	254	254	259	259
24"	0.750		186.41	241	241	241	241	234	234	239	239

Disclaimer: The above referenced tabulations and weights are merely intended as a reference guide and are not a representation or warranty by the seller for the approximate weights, lengths and number of pipe joints to be utilized in the loading process by transporters or their customers. Transporter is ultimately responsible for the determination of appropriate weight bearing and load capacities.

(713) 799-9235
 FAX (713) 799-8701
 Web Site: www.texaspipe.com
 E-mail: tps@texaspipe.com